


InfiLINK XG Um/2X.500.2x500

Description	InfiLINK XG Um/2X.500.2x500, 2 GHz point-to-point unit, net throughput up to 500 Mbps, 2x N-type (F) connectors for external antenna
Net throughput	up to 500 Mbps
Recommended distances	up to 100 km
Radio technology	MIMO 2x2, Cyclic single carrier
Modulation coding schemes	from QPSK 1/4 to QAM1024 8/10
Transmit power	up to 27 dBm
Receiver sensitivity	down to -94 dBm
Frequency range	1990-3010 MHz
Channel width	10, 20, 40 MHz
Center frequency adjustment step	1 MHz
Duplex scheme	TDD, Hybrid-FDD
Wired Interfaces	2x GigabitEthernet, SFP



InfiLINK XG Um/2X.500.2x500

Consumption	up to 30 W
Power options	90-240 VAC @ 50/60 Hz, 43..56 VDC
Outdoor Unit (ODU)	256 x 240 x 86 mm, 2.1 kg
	
Packing List	<ul style="list-style-type: none"> - Outdoor unit Um/2X.500.2x500 - 1 pcs. - Power Supply IDU-BS-G(60W) - 1 pcs. - Power Cord - 1 pcs. - Cable Gland for RJ-45 - 2 pcs. - Cable Gland for optical cable - 1 pcs. - Standard RJ-45 connector - 2 pcs. - Shielded RJ-45 connector - 1 pcs. - RJ-45 Plug Cap - 1 pcs. - MONT-KIT-85 Mounting kit - 1 pcs. - Quick Start Guide - 1 pcs.



InfiLINK XG Um/2X.500.2x500

Features

RADIO

- ▶ **Best-in-breed spectral efficiency**
 - up to 14 bps/Hz
 - real throughput in excess of 130 Mbps in just 10 MHz of spectrum
- ▶ **High transmit power and perfect sensitivity even at the highest-order modulations**
 - Reliable signal receiving in both LOS and NLOS conditions
- ▶ **Superior interference and noise immunity**
 - High-selectivity receiver with channel filtering cuts off in-band interference
- ▶ **TDD synchronization using a built-in GNSS receiver**

NETWORKING

- ▶ **Built-in full-fledged L2 switch supporting VLAN and STP**
- ▶ **Transparent L2 transport for Ethernet traffic of any type**

MANAGEMENT FEATURES

- ▶ **Web-based graphical user interface**
- ▶ **Command line interface**
- ▶ **SNMP v1/2c/3 support (MIB-II and proprietary MIBs)**
- ▶ **Centralized monitoring using EMS InfiMONITOR.**

QUALITY-OF-SERVICE

- ▶ **QoS support:**
 - 4 priority queues: strict and weighted prioritisation
 - Classification based on IEEE 802.1p
 - Egress rate limiting on each network port

INSTALLATION AND DIAGNOSTIC TOOLS

- ▶ **LED indication**
 - power status
 - wired and wireless link status
 - received signal strength indication
 - TDD sync status
- ▶ **Web GUI tools**
 - antenna alignment tool
 - spectrum analyzer



InfiLINK XG Um/2X.500.2x500

Features

ENVIRONMENTAL

- ▶ **Outdoor unit:**
 - Operating temperature range $-40..+60^{\circ}\text{C}$, (can be extended to $-55..+60^{\circ}\text{C}$, models with "t" index in PN)
 - IP66/IP67 compliant water and dust protection
- ▶ **Indoor unit:**
 - 100-240 VAC ~ @ 50/60 Hz or $\pm 43.. \pm 56$ VDC, 802.3at compliant
 - power consumption up to 60 W

STANDARD COMPLIANCE

- ▶ **Safety:**
 - EN 60950-1:2006, UL 60950-1 2nd ed.
- ▶ **Radio (pending):**
 - EN 302 326-2
- ▶ **EMC:**
 - ETSI EN 301 489-1, ETSI EN 301 489-17, FCC Part 15 Class B
- ▶ **RoHS:**
 - Directive 2011/65/EU

